

## IC-F29SR2 Licence-free Radio Features

### 16<sup>ch</sup> 16 Usable Channels

The IC-F29SR2 meets the European standard EN 300 296 and has total of 16 channels including new 8 channels\*.  
\* New 8 channels may be restricted, depending on countries.

### 1500mW Ultra Powerful Audio

Icom custom high power handling capacity speaker for 1500 mW powerful audio. Hear calls destined for you in all sorts of environments.

### Rotary Channel

Up to 32 operating channels and group code (16 ch x 2 zones) can be programmed to the 16-position rotary channel knob. The operating zone can be switched with the top red button.

### Call-Ring

The Call-Ring function can be used to call receivers with a ringer tone. Ten different ring patterns can be selected.

### Answer Back

The Smart-Ring function checks whether the receiver is in communication range with a ringer sound.

### Private Conversation

The built-in inversion voice scrambler provides private conversation. Up to 16 codes are selectable.

### 21 Hours Operation

The supplied Li-Ion battery pack, BP-279, provides up to 21 hours of operating time. The supplied rapid charger BC-213 charges the BP-279 in 2.5 hours.

### Group Call

The user programmable CTCSS and DTCS codes can be used for group call. You will only send a call to specified group members using the same tone and same channel.

### Other Features

- Low battery alert
- Monitor function
- Surveillance function
- Microphone gain level adjustment
- Channel/zone announcement
- Time-out-timer function
- Siren alarm function
- Key lock function
- Power on scan function
- PC programmable

## Specifications

- Usable channels: 16 channels
- Output power: 500 mW (ERP)
- Audio output power: Internal speaker 1500 mW typ. (with 8 Ω load)  
External speaker 400 mW typ. (with 8 Ω load)  
(at 5% distortion)
- Dimensions: 52.2 (W) x 186.1 (H) x 24.5 (D) mm (with BP-279)
- Weight: 240 g (with BP-279)
- Communication range\*: Approx. 8 km (Wide open space)
- Operating temperature: -25°C to +55°C
- IP rating: IP67 (Dust-tight and waterproof protection)
- Military standard: MIL-STD-810-G

\* Communication range may differ depending on operating environment or weather conditions, etc.

**All stated specifications are subject to change without notice or obligation.**

## Supplied Accessories



AC adapter  
BC-123SE/SUK\*



Rapid charger  
BC-213



Battery pack  
BP-279



Belt clip  
MB-133

(\* May differ depending on version)

## Batteries & Charger Options



BP-278 BP-279 BP-280

Battery packs	Type	Capacity	Operating time*
BP-278	Rechargeable Li-ion 7.2 V	1130 mAh (min.) 1190 mAh (typ.)	Up to 16 hours
BP-279	Rechargeable Li-ion 7.2 V	1485 mAh (min.) 1570 mAh (typ.)	Up to 21 hours
BP-280	Rechargeable Li-ion 7.2 V	2280 mAh (min.) 2400 mAh (typ.)	Up to 33 hours

\* Tx: Rx: standby = 5 : 5 : 90 duty cycle. Power save ON.



Multi-charger  
BC-214



Cigarette lighter cable & power supply cable  
OPC-656



Charger bracket  
CP-23L



Charger bracket  
MB-130

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand, and/or other countries.

Icom Inc.

Count on us!

Your local distributor/dealer:

Icom France s.a.s.  
<http://www.icom-france.com>

ICOM



16<sup>ch</sup>  
PMR446  
PROFESSIONAL LICENCE-FREE

IP67

Rugged  
MIL-STD 810

PMR446 TRANSCEIVER

IC-F29SR2

Compact & Slim  
IP67 Waterproof  
Tough & Rugged




1500 mW  
Powerful  
Audio

ACTUAL  
SIZE

PMR446 TRANSCEIVER  
**IC-F29SR2**

## Extensive Optional Accessories

Our range of optional Icom microphones and headsets increases the flexibility of your team in the workplace.





Retail  
& Hospitality

### Earphone-microphones

**HM-153LA**  
Durable lapel microphone with earphone for low-profile, discreet placement.



PTT lock switch



Lapel clip

**HM-166LA**  
Light weight lapel microphone with earphone.



Facility  
& Security Guard

### Speaker-microphones

**HM-168LWP**  
IP67 waterproof speaker-microphone for outdoor work or places prone to getting wet.

IP67



Earphone jack



**HM-159LA**  
Full size, durable speaker-microphone provides loud audio.



Earphone jack

**HM-158LA**  
Lightweight, compact size speaker-microphone.




Manufacturing  
& Construction

### Headsets

**HS-94LWP**

Earhook headset with boom microphone and waterproof connector. Provides hands-free operation.



**HS-95LWP**

Behind-the-head type with boom microphone and waterproof connector. Provides hands-free operation.

**HS-97 + VS-4LA or OPC-2004LA**  
Throat microphone picks up your speech vibration even in a noisy environment.

VS-4LA



**VS-4LA PTT SWITCH CABLE**  
**OPC-2004LA PLUG ADAPTER CABLE**  
Either VS-4LA or OPC-2004LA is required when using HS-97 headset.